

H&H Aluminum Trailers



WWW.HHTRAILER.COM



H&H Trailers, LLC

All Aluminum Production Models

**Limited Warranty on Frame, Tongue, and Crossmembers:
Standard Models – 3 years**



Table of Contents

PAGE	1	GCA GOLF CAR TRAILER
PAGE	2	AMS BIKE TRAILER
PAGE	3	ALS & ALST OPEN SLED TRAILERS
PAGE	4	RSA RAIL SIDE SINGLE AXLE UTILITY TRAILERS
PAGE	5	RSA RAIL SIDE TANDEM AXLE UTILITY TRAILERS
PAGE	6	SSA SOLID SIDE SINGLE AXLE UTILITY TRAILERS
PAGE	7	SSA SOLID SIDE TANDEM AXLE UTILITY TRAILERS
PAGE	8	HDA HEAVY DUTY FLATBED TRAILERS
PAGE	9	SPEED LOADER™ MXA & EXA TANDEM TILTBEDS
PAGE	11	HAL HI-DECK TANDEM AXLE TRAILERS

Please note: H&H Trailers® does not recommend using utility trailers as car haulers. Fold-forward storage option on ramp gates is intended for storage only, not while hauling.

PLEASE NOTE: H&H TRAILERS, LLC STRONGLY RECOMMENDS HITCHING YOUR TRAILER TO YOUR TOW VEHICLE BEFORE LOADING!

PHOTOS MAY SHOW OPTIONAL EQUIPMENT. MODELS AND OPTIONS ARE SUBJECT TO CHANGE.

THIS PAGE LEFT BLANK INTENTIONALLY.

H&H GCA Aluminum Golf Car Trailer

STANDARD FEATURES

- Constructed of 100% 6061-T6 Aluminum Extrusion Billet.
- 60" Between Fenders and 8' Long.
- Aluminum Plank Deck.
- Multiple Stake Pockets.
- 6061-T6 Aluminum Extruded Billet Tube Tongue with Gusseted Drop Neck.
- 2" Self Latching Posi-Lock Coupler.
- Extra Long, Plated Safety Chains.
- 2000lb Swivel-Up Jack.
- 1500lb Capacity.
- High Speed Rated 20.5x8x10 Tires on 5-bolt Pattern Wheels.
- Aluminum Fenders with Anti-Splash Backs.
- Aluminum Plank Bi-Fold Ramp Gate.
- LED Tail and Marker Lights.



<u>MODEL</u>	<u>DESCRIPTION</u>
58GCA.....	5'X8' aluminum deck & rear ramp gate



Upgrade Options
Spare Wheel and Tire
Wheel Chock

THIS PAGE LEFT BLANK INTENTIONALLY.

H&H AMS Aluminum Bike Trailer

STANDARD FEATURES

- 3"x2" Angle aluminum extrusion lower main frame. Channel aluminum frame.
 - 3"x2" Angle aluminum extrusion crossmembers.
 - Rectangular aluminum extrusion tube uprights & top rail – 5 ½" tall.
 - 4" Aluminum channel tongue with 2"x2" aluminum angle cross brace.
- Custom designed, angled front end with a custom, removable rock guard fairing.
 - 2" A-frame, posi-lock coupler with safety chains.
 - 2000lb swivel-up jack.
 - Full DOT compliant, LED lighting.
 - Sealed wiring harness.
- 3500lb spring idler axle with EZ-lube hubs - 2990lb GVWR.
 - ST205/75R15 radial tires on 15" aluminum mod wheels.
 - Extruded aluminum planked decking.
- 54" long aluminum bi-fold ramp with spring loaded J-hooks and no gaps – 1500lb load rating.
- D-ring tie downs and wheel chock to help secure motorcycle.



MODEL	DECK WIDTH	DECK LENGTH
AMS 5.5X8 SA	66"	8'
AMS 5.5X10 SA	66"	10'

Upgrade Options

- Brake Axle
- Aluminum Hollow Spoke, Spider Spoke or Black Mamba Wheels
- Spare & Spare Mount



H&H ALS Aluminum Open 2-Place Sled Trailer

STANDARD FEATURES

- 4" Channel aluminum frame.
- 2" Channel aluminum crossmembers.
- Aluminum extrusion side tie rails.
- 24" V-nose front.
- 101" Wide, 2 place sled deck.
- 4"x 2" Aluminum tongue with gusseted drop neck.
- Extended tongue length, approx. 5ft overall.
- 2" Posi-lock coupler with safety chains.
- 2000lb swivel-up jack.
- Full DOT compliant, LED lighting.
- 2990lb spring idler axle - 2990lb GVWR.
- ST175/80D13 bias tires on white wheels.
- 3/4" Treated plywood deck – 96" wide.
- Ski hold-downs – aluminum tube bars with hold-down cranks that bolt directly to the frame.
- 54" long aluminum ramp – stowed under the rear deck and hooks onto the front and rear for easy loading and unloading.



MODEL

SLED 101X12V ALUM

DESCRIPTION

101"x12' V-Nose 2' – 2 Place Aluminum Open Sled Trailer

*Ramp & Carrier Standard!
Rear Loading & Front Unloading*



Upgrade Options

Extruded Aluminum Plank Floor
2 Bi-fold Front Ramp Gates with Offset Slats
Spare Wheels and Tire

**Help Protect Your Sleds!
Add Front Bi-Fold Ramp Gates that Double as a Fairing.**

H&H ALST Aluminum Open 4-Place Sled Trailer



Model shown with optional Front Sled Ramp Gates and Ramps in Carrier.

STANDARD FEATURES

- 5" Aluminum double-hollow tube frame.
- 2" Aluminum channel crossmembers.
- Aluminum extrusion side rails.
- 4"x 3" Aluminum tube tongue with gusseted drop neck.
- Extended tongue length for optional front ramp clearance.
- 2" Posi-lock coupler with safety chains.
- 2000lb swivel-up jack.
- Full DOT compliant, LED lighting.
- Tandem electric brake axles – 4500lb GVWR.
- ST175/80D13 bias tires on white wheels.
- 24" V-nose front.
- 101" Wide, 4 place sled deck - 3/4" treated plywood deck.
- Ski hold-downs – aluminum tube bars with hold-down cranks that bolt directly to the frame.
- 54" long aluminum ramp – stowed under the rear deck and hooks onto trailer for easy loading and unloading.
- D-ring package.

MODEL	DESCRIPTION
SLED ALST 101X24V ALUM	101"x24' V-Nose 2' – 4 Place Aluminum Open Sled Trailer



Upgrade Options

- Extruded Aluminum Plank Floor
- Front Sled Ramp Gates with ATP
- 2 Bi-fold Front Ramp Gates with Offset Slats
- 7000lb GVWR
- Aluminum Wheels
- Spare Wheels and Tire

H&H RSA Rail Side Single Axle Utility Trailers



Model shown with optional bi-fold gate

STANDARD FEATURES

- 14" tall side aluminum rails.
- Angle 6061-T6 aluminum extrusion lower frame.
- Rectangular aluminum tube uprights and top rail.
- 4" channel aluminum tongue with brace.
- 2" A-frame coupler with dual safety chains.
- 2000lb coupler mounted jack.
- Treated 2x8 wood decking.
- Aluminum radius fenders.
- 3500lb idler axle with EZ lube hubs– 2990lb GVWR.
- ST205/75R15 radial tires on white wheels.
- 54" long, aluminum ramp gate with spring loaded J-hooks with no pin removal – 1500lb rating.
- Full LED lighting.
- Wiring enclosed in conduit.

MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
RSA 5x8F RS	5x8' Rail Side Aluminum Flatbed RSA	60"	8ft
RSA 5x10F RS	5x10' Rail Side Aluminum Flatbed RSA	60"	10ft
RSA 5x12F RS	5x12' Rail Side Aluminum Flatbed RSA	60"	12ft
RSA 5x14F RS	5x14' Rail Side Aluminum Flatbed RSA	60"	14ft
RSA 5.5x10F RS	5.5x10' Rail Side Aluminum Flatbed RSA	66"	10ft
RSA 5.5x12F RS	5.5x12' Rail Side Aluminum Flatbed RSA	66"	12ft
RSA 5.5x14F RS	5.5x14' Rail Side Aluminum Flatbed RSA	66"	14ft
RSA 8x10F RS	8x10' Rail Side Aluminum Flatbed RSA	76"	10ft
RSA 8x12F RS	8x12' Rail Side Aluminum Flatbed RSA	76"	12ft
RSA 8x14F RS	8x14' Rail Side Aluminum Flatbed RSA	76"	14ft
RSA 8.5x10F RS	8.5x10' Rail Side Aluminum Flatbed RSA	82"	10ft
RSA 8.5x12F RS	8.5x12' Rail Side Aluminum Flatbed RSA	82"	12ft
RSA 8.5x14F RS	8.5x14' Rail Side Aluminum Flatbed RSA	82"	14ft

Upgrade Options

- Extruded Aluminum Plank Deck
- Bi-fold Ramp Gate Upgrade
- 60" Wide Side Ramp Gate – 12ft minimum
- ATV Ramps – 12ft minimum
- 3500lb Brake Axle Upgrade
- Aluminum Wheels
- Spare Wheel and Tire
- Wheel Check



ATV Ramps

H&H RSA Rail Side Tandem Axle Utility Trailers



Model shown with optional bi-fold gate



STANDARD FEATURES

- 14" tall side aluminum rails.
- 6061-T6 billet extruded aluminum angle lower frame.
- Rectangular aluminum tube uprights and top rail.
- 5" channel aluminum tongue with brace.
- 2 5/16" A-frame coupler with dual safety chains.
- 5000lb A-frame jack.
- Treated 2x8 wood decking.
- Aluminum teardrop fenders.
- Tandem 3500lb spring axles with EZ lube hubs.
- 7000lb GVWR.
- 4-wheel electric brakes with break-away kit and battery.
- ST205/75R15 radial tires on white wheels.
- 54" long, aluminum lay-down ramp gate with spring loaded J-hooks with no pin removal – 1500lb rating.
- LED tail and marker lights with wiring enclosed in conduit.

H&H does not recommend utility trailers for hauling cars.

MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
TRSA8 UT 12 RS	8x12' Rail Side Aluminum Tandem RSA	76"	12ft
TRSA8 UT 14 RS	8x14' Rail Side Aluminum Tandem RSA	76"	14ft
TRSA8 UT 16 RS	8x16' Rail Side Aluminum Tandem RSA	76"	16ft
TRSA8 UT 18 RS	8x18' Rail Side Aluminum Tandem RSA	76"	18ft
TRSA8 UT 20 RS	8x20' Rail Side Aluminum Tandem RSA	76"	20ft
TRSA8.5 UT 12 RS	8.5x12' Rail Side Aluminum Tandem RSA	82"	12ft
TRSA8.5 UT 14 RS	8.5x14' Rail Side Aluminum Tandem RSA	82"	14ft
TRSA8.5 UT 16 RS	8.5x16' Rail Side Aluminum Tandem RSA	82"	16ft
TRSA8.5 UT 18 RS	8.5x18' Rail Side Aluminum Tandem RSA	82"	18ft
TRSA8.5 UT 20 RS	8.5x20' Rail Side Aluminum Tandem RSA	82"	20ft

Upgrade Options

- Extruded Aluminum Plank Deck
- Bi-fold Ramp Gate Upgrade
- 60" Wide Side Ramp Gate – 16ft minimum
- ATV Ramps – 14ft minimum
- Aluminum Wheels
- Torsion Axle
- Spare Wheel and Tire
- Wheel Chock
- Toolbox



Side Ramp Gate



ATV Ramps

Low Maintenance... Long Lasting... Good Looking

H&H SSA Solid Side Single Axle Utility Trailers

STANDARD FEATURES

- 15" tall formed 1/8" polished aluminum diamond plate main body.
- 4" channel aluminum tongue.
- 2" A-frame Posi-Lock coupler.
- 2000lb swivel-up jack.
- .060 aluminum radius fenders.
- 3500lb axle with leaf spring suspension & EZ lube hubs – 2990lb GVWR.
- ST205/75R15 radial tires on white wheels.
- Treated 2x8 wood decking.
- 54" long, aluminum lay down gate with spring loaded J-hooks. 1500lb load rating.
- LED tail and marker lights with wiring enclosed in conduit.



MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
SSA 5 X8F SS.....	5x8' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	8ft
SSA 5 X10F SS.....	5x10' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	10ft
SSA 5 X12F SS.....	5x12' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	12ft
SSA 5 X14F SS.....	5x14' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	14ft
SSA 5.5 X10F SS.....	5.5x10' Aluminum Flatbed SSA Solid Panel Sides single axle	66"	10ft
SSA 5.5 X12F SS.....	5.5x12' Aluminum Flatbed SSA Solid Panel Sides single axle	66"	12ft
SSA 5.5 X14F SS.....	5.5x14' Aluminum Flatbed SSA Solid Panel Sides single axle	66"	14ft
SSA 8 X10F SS.....	8x10' Aluminum Flatbed SSA Solid Panel Sides single axle	76"	10ft
SSA 8 X12F SS.....	8x12' Aluminum Flatbed SSA Solid Panel Sides single axle	76"	12ft
SSA 8 X14F SS.....	8x14' Aluminum Flatbed SSA Solid Panel Sides single axle	76"	14ft
SSA 8.5 X10F SS.....	8.5x10' Aluminum Flatbed SSA Solid Panel Sides single axle	82"	10ft
SSA 8.5 X12F SS.....	8.5x12' Aluminum Flatbed SSA Solid Panel Sides single axle	82"	12ft
SSA 8.5 X14F SS.....	8.5x14' Aluminum Flatbed SSA Solid Panel Sides single axle	82"	14ft

33% Less Weight than Steel!



Box Top Rope Rail & Bi-fold Ramp Gate

Upgrade Options

- Extruded Aluminum Plank Deck
- Bi-fold Ramp Gate Upgrade
- 60" Wide Side Ramp Gate – 12ft minimum
- Box Top Rope Rail
- Aluminum Stake Pockets
- Electric Brake Axle with Break-away Safety Kit and Battery
- Aluminum Wheels
- Spare Wheel and Tire
- Wheel Chock

H&H SSA Solid Side Tandem Axle Utility Trailers



Model shown with optional bi-fold gate



STANDARD FEATURES

- 15" tall formed 1/8" polished aluminum diamond plate main body.
- 5" channel aluminum tongue.
- 2⁵/₁₆" A-frame Posi-Lock coupler.
- 5000lb recessed jack in set-back position.
- .060 teardrop aluminum fenders.
- Tandem 3500lb spring axles with EZ lube hubs – 7000lb GVWR.
- 4-wheel electric brakes with break-away kit & battery.
- ST205/75R15 radial tires on white wheels.
- Treated 2x8 wood decking.
- 54" Long, aluminum lay down ramp gate with spring loaded j-hooks. 1500lb load rating.
- LED tail and marker lights with wiring enclosed in conduit.

Full Polished Aluminum Body

MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
SSA8 UT 12 SS.....	8x12' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	76"	12ft
SSA8 UT 14 SS.....	8x14' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	76"	14ft
SSA8 UT 16 SS.....	8x16' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	76"	16ft
SSA8 UT 18 SS.....	8x18' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	76"	18ft
SSA8 .5UT 12 SS.....	8.5x12' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	82"	12ft
SSA8 .5UT 14 SS.....	8.5x14' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	82"	14ft
SSA8 .5UT 16 SS.....	8.5x16' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	82"	16ft
SSA8 .5UT 18 SS.....	8.5x18' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	82"	18ft
SSA8 .5UT 20 SS.....	8.5x20' Aluminum SSA Solid 15" Panel Sides tandem trailer.....	82"	20ft



Spring Loaded J hooks Standard
Unlatch ramp with no clip removal!

- Upgrade Options**
- Extruded Aluminum Plank Deck
 - Bi-fold Ramp Gate Upgrade
 - 60" Wide Side Ramp Gate – 16' minimum
 - Box Top Rope Rail
 - Aluminum Stake Pockets
 - Torsion Axles
 - Aluminum Wheels
 - Spare Wheel and Tire
 - Wheel Chock
 - Toolbox



Extruded Aluminum Plank Deck Option

H&H HDA Heavy Duty Flatbed Trailers

Standard Features

- 6" aluminum channel tongue & frame.
- 3" aluminum channel crossmembers.
- Powder coated steel substructures.
- 2⁵/₁₆" A-frame Posi-Lock coupler with dual safety chains.
- 5000lb set-back jack.
- Treated 2x8 wood decking.
- Rectangular aluminum tube headache rack.
- Multiple stake pocket tie-downs with rub rails.
- 6061-T6 Billet aluminum extruded 5' 3" ramps with carrier.
- Removable teardrop fenders.
- Tandem 3500lb spring axles with EZ lube hubs – 7000lb GVWR
- 4-wheel electric brakes with break-away kit & battery.
- ST205/75R15 radial tires on white wheels.
- Full LED lighting system with Slimline LED taillights.
- Sealed wiring harness.



MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
8.5 HDA16 AL	8.5x16' HDA Aluminum Heavy Duty Flatbed	82"	16ft
8.5 HDA18 AL	8.5x18' HDA Aluminum Heavy Duty Flatbed	82"	18ft
8.5 HDA20 AL	8.5x20' HDA Aluminum Heavy Duty Flatbed	82"	20ft
*8.5 HDA22 AL	8.5x22' HDA Aluminum Heavy Duty Flatbed	82"	22ft
*8.5 HDA24 AL	8.5x24' HDA Aluminum Heavy Duty Flatbed	82"	24ft

*10K Suspension Package Required on 22' & 24' models.

Excellent Corrosion Resistance, Strength, & Longevity

Upgrade Options	Description
Extruded Aluminum Decking	Plank style.
2' All Aluminum Dovetail	Full aluminum dovetail.
2' Aluminum Dovetail with Wood Deck	Aluminum framed wood dovetail.
9990lb GVWR	Includes tandem 5200lb brake axles, 8" channel aluminum frame upgrade, 14" on center crossmember spacing, drop-down dock legs, ST225/75R15 radials on 6-bolt white wheels, break-away kit with battery. (Required on 22' & 24' models)
12000lb GVWR	Includes tandem 6000lb brake axles, 8" channel aluminum frame upgrade, 14" on center crossmember spacing, drop-down dock legs, ST235/80R16 radials on 8-bolt white wheels, break-away kit with battery, DOT reflective tape.
14000lb GVWR	Includes tandem 7000lb brake axles, 8" channel aluminum frame upgrade, 4" channel crossmembers, 14" on center cross member spacing, drop-down dock legs, ST235/80R16 radials on 8-bolt white wheels, break-away kit with battery, DOT reflective tape.
Aluminum Wheels	Upgrade to radial tires on aluminum wheels.
Rock Guard Car Fairing	Powder-coated steel tube and formed ATP.
Custom Aluminum Toolbox	0.100 Aluminum Tread Bright with lockable stainless steel paddle latch.

Additional options may be available.

H&H Speed Loader™ MXA & EXA Tiltbeds

Manually (MXA) Operated Hydraulic Tiltbed or Fully Electric (EXA) Hydraulic Tiltbed



WARNING: H&H DOES NOT RECOMMEND TILTING THE SPEEDLOADER™ BED WHEN THE TRAILER IS NOT COUPLED TO THE TOW VEHICLE.

STANDARD FEATURES

- 6" aluminum channel tongue and frame.
- 3" aluminum channel cross members.
- 7000lb dropleg jack.
- Removable aluminum teardrop fenders.
- 2x8 treated wood decking.
- Rectangular aluminum tube headache rack.
- Multiple stake pocket tie-downs with rub rails.
- *Tandem 3500lb spring axles with EZ lube hubs – 7000lb GVWR.
- 4-wheel electric brakes with break-away kit & battery.
- ST205/75R15 radial tires on white wheels.
- All steel bracing and attaching parts feature a durable powder coat finish for electrolysis resistance.
- Full LED lighting system with Slimline LED taillights.
- Sealed wiring harness.

MODEL	DESCRIPTION	WIDTH	LENGTH
T8.5HD18 MXA MAN/HYD	8.5x18' MXA Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	18ft
T8.5HD20 MXA MAN/HYD	8.5x20' MXA Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	20ft
*T8.5HD22 MXA MAN/HYD	8.5x22' MXA Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	22ft
*T8.5HD24 MXA MAN/HYD	8.5x24' MXA Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	24ft
*ONLY AVAILABLE WITH 10K PACKAGE.			
T8.5HD16 MXLA MAN/HYD	8.5x16' MXLA LO-PRO Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	16ft
T8.5HD18 MXLA MAN/HYD	8.5x18' MXLA LO-PRO Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	18ft
T8.5HD20 MXLA MAN/HYD	8.5x20' MXLA LO-PRO Aluminum Speed Loader™ Manual Tandem Tiltbed	82"	20ft
<i>L-models will include 4" dropped axles, low profile tongue; 4" raise coupler, and 3-degrees less lean angle.</i>			
T8.5HD18 EXA HYD/ELEC	8.5x18' EXA Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	18ft
T8.5HD20 EXA HYD/ELEC	8.5x20' EXA Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	20ft
*T8.5HD22 EXA HYD/ELEC	8.5x22' EXA Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	22ft
*T8.5HD24 EXA HYD/ELEC	8.5x24' EXA Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	24ft
*ONLY AVAILABLE WITH 10K PACKAGE.			
T8.5HD16 EXLA HYD/ELEC	8.5x16' EXLA LO-PRO Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	16ft
T8.5HD18 EXLA HYD/ELEC	8.5x18' EXLA LO-PRO Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	18ft
T8.5HD20 EXLA HYD/ELEC	8.5x20' EXLA LO-PRO Aluminum Speed Loader™ Electric Tandem Tiltbed	82"	20ft
<i>L-models will include 4" dropped axles, low profile tongue, 4" raised coupler, and 3-degrees less lean angle.</i>			

Upgrade Options	Description
9990lb GVWR	Includes tandem 5200lb brake axles, 8" channel aluminum frame upgrade, 14" on center crossmember spacing, ST225/75R15 radials on 6-bolt white wheels, break-away kit with battery.
12000lb or 14000lb GVWR	Includes tandem 6000lb or 7000lb brake axles, 8" channel aluminum frame upgrade, 14" on center crossmember spacing, ST235/80R16 radials on 8-bolt white wheels, break-away kit with battery, DOT reflective tape.
Aluminum Wheels	Upgrade to radial tires on aluminum wheels.
Rock Guard Car Fairing	Powder-coated steel tube and formed ATP.
Extruded Aluminum Flooring	Planked style.
Custom Aluminum Toolbox	.100 Aluminum Tread Bright with lockable stainless steel paddle latch.
10K Electric Super Winch	Includes cable, hook, remote, and power cables. Battery sold separately.
2-Way Cordless Remote	For electric winch or EXA electric tiltbed.
<i>Additional options may be available.</i>	

THIS PAGE LEFT BLANK INTENTIONALLY.

H&H HAL Hi-Deck Trailers



Model shown with optional dovetail.

Standard Features

- 5" aluminum channel tongue & frame.
- 3" aluminum channel crossmembers on 28" on center spacing.
- Headache rack.
- 2⁵/₁₆" adjustable height coupler with dual safety chains.
- 7000lb drop leg jack – set-back with foot.
- Treated wood decking with board end caps.
- Multiple stake pocket tie-downs with rub rails.
- Tandem 3500lb spring axles with EZ lube hubs.
- 7000lb GVWR.
- 4-wheel electric brakes with break-away kit & battery.
- ST205/75R15 radial tires on white wheels with mud flaps.
- Full LED lighting system.
- Sealed wiring harness.

MODEL	DESCRIPTION	DECK WIDTH	OVERALL DECK LENGTH
HAL 14 AL	102"x14' Aluminum Hi-Deck	102"	14ft
HAL 16 AL	102"x16' Aluminum Hi-Deck	102"	16ft
HAL 18 AL	102"x18' Aluminum Hi-Deck	102"	18ft
HAL 20 AL	102"x20' Aluminum Hi-Deck	102"	20ft

Upgrade Options

Description

9990lb	Includes (2) 5200lb brake axles, 6" channel aluminum frame, 14" on center cross member spacing, ST225/75R15 radials on 6-bolt white wheels, DOT tape, drop-down dock legs.
12000lb or 14000lb GVWR	Includes (2) 6000lb or (2) 7000lb brake axles, 6" channel aluminum frame, 14" on center cross member spacing, ST235/80R16 radials on 8-bolt white wheels, DOT tape, drop-down dock legs.
Extruded Aluminum Flooring	Planked style.
4ft Dovetails	4' Aluminum self-cleaning fixed dovetail.
(2) 3"x5' Aluminum Ramps & Carrier	1500lb load rating each.
Spring Assisted Skid Loader Ramps	3"x 5' steel powder coated skid loader ramps – recommended on 10K-14K upgrades).
Aluminum Wheels	Mod, 5-star, Hollow Spoke or Spider Spoke.
Spare Tire & Wheel	
Tie-downs	D-rings or E-track.
<i>Additional options may be available.</i>	



H&H Trailers, LLC

222 N. 1st Street, Clarinda, IA 51632

712.542.2618 P 712.542.2707 F

www.hhtrailer.com

MANUFACTURED IN CLARINDA, IOWA, U.S.A

H&H Trailers®, the wing logo, & Speed Loader™ are registered trademarks of H&H Trailers LLC. ©2010-2014 H&H Trailers LLC. All rights reserved.
Published 10/01/2014

